



20 cu. ft. 36-Inch Width Counter-Depth French Door Refrigerator with Interior Dispense

KRFC300EBS

Available Finishes/Colours

- KRFC300EBS  
Black Stainless Steel with PrintShield™ Finish
- KRFC300ESS  
Stainless Steel
- KRFC300EWH  
White

Dimensions		Details	
Depth	29 3/8	Cooling Type	Single Evaporator
Height	70 1/8	Counter Depth	Yes
Width	35 3/4	Door Style	Contour
AHAM Volumes And Shelf Area		Controls	
Freezer Volume (Cu Ft)	5.62	Control Type	Electronic
Refrigerator Volume (Cu Ft)	14.38	Air Filter Indicator/Reset	No
Configuration and Overview		Automatic Defrost	Yes
Advance Foam Insulation	99.9% lower Global Warming Potential and Better Energy Performance	Verrouillage des commandes	No
Counter Depth	Yes	LCD Touch Screen	No
Number of Doors	3	Door Ajar/Open Alarm	Yes
Compatibility		Control Lockout	No
Connectivity	No	Control Location	Interior Up Front
Works With	No	Max Cool/Fast Cool	Yes
Details			
Advance Foam Insulation	99.9% lower Global Warming Potential and Better Energy Performance		

This 20 cubic foot refrigerator has a counter-depth design that gives it a built-in look. But the beauty of this French door refrigerator goes beyond the exterior. The ExtendFresh™ Temperature Management System and Produce Preserver help keep food fresh. LED lighting throughout the refrigerator makes food easy to find on every level.

- Top Features
- ExtendFresh™ Plus Temperature Management System
- Interior Water Dispenser
- Humidity Controlled Crispers

- Manuals & Literature:
-  [Dimension Guide](#)

 [Energy Guide](#)

 [Use and Care Guide](#)

 [Warranty Information](#)

## Bottom Mount Refrigerator

### PRODUCT MODEL NUMBERS

KBFS20EC KBFS25EC  
KBFS22EC KRFC300E  
KRFF302E KRFF305E

**Electrical:** A 115-volt, 60-Hz, AC-only, 15- or 20-amp fused, grounded electrical supply is required. It is recommended that a separate circuit serving only your refrigerator be provided. Use an outlet that cannot be turned off by a switch. Do not use an extension cord.



**NOTE:** Before performing any type of installation, cleaning, or removing a light bulb, turn the control (Thermostat, Refrigerator or Freezer Control depending on the model) to OFF and then disconnect the refrigerator from the electrical source. When you are finished, reconnect the refrigerator to the electrical source and reset the control (Thermostat, Refrigerator or Freezer Control depending on the model) to the desired setting. See "Using the Controls."

**Water:** A cold water supply with water pressure between 35 and 120 psi (241 and 827 kPa) is required to operate the ice maker and water dispenser. If you have questions about your water pressure, call a licensed, qualified plumber.

**IMPORTANT:** The pressure of the water coming out of a reverse osmosis system going to the water inlet valve of the refrigerator needs to be between 35 and 120 psi (241 and 827 kPa).


**Reverse Osmosis Water Supply:** If a reverse osmosis water filtration system is connected to your cold water supply, the water pressure to the reverse osmosis system needs to be a minimum of 40 to 60 psi (276 to 414 kPa).

### PRODUCT DIMENSIONS



Model Number/Size	Height - Overall "A"	Height - Top of Cabinet "B"	Depth - Doors Open 90° "C"	Depth - Drawer Open "D"	Depth - With Handles "E"	Depth - Without Handles "F"	Depth - Cabinet Only "G"	Width - Cabinet "H"
KBFS20EC 20.0 cu. ft.	70 1/8" (178.1 cm)	68 1/8" (174.0 cm)	43" (109.2 cm)	44 1/8" (113 cm)	29 3/8" (74.6 cm)	28" (71.1 cm)	24 1/8" (61.3 cm)	35 5/8" (90.5 cm)
KBFS22EC (21.7 cu. ft.)	70 1/8" (178.1 cm)	68 13/16" (174.8 cm)	47 1/8" (119.5 cm)	52 1/8" (132.2 cm)	34 7/8" (87.5 cm)	31 15/16" (81.1 cm)	28 1/8" (71.4 cm)	32 5/8" (82.9 cm)
KBFS25EC (24.8 cu. ft.)	70 1/8" (178.1 cm)	68 13/16" (174.8 cm)	48 1/8" (122.1 cm)	53 1/8" (135 cm)	35 7/8" (90 cm)	32 15/16" (83.7 cm)	29 1/8" (74 cm)	35 5/8" (90.5 cm)
KRRC300E (20 cu. ft.)	70 1/8" (178.1 cm)	68 7/8" (174.9 cm)	43 1/8" (109.5 cm)	48 1/8" (122.2 cm)	30 1/8" (77.5 cm)	28" (71.1 cm)	24 1/8" (61.3 cm)	35 3/8" (90.8 cm)
KRFF302E (22.1 cu. ft.)	70 1/8" (178.1 cm)	68 7/8" (174.9 cm)	47 1/8" (122.2 cm)	52 1/8" (134.9 cm)	34 1/8" (90.2 cm)	32" (83.8 cm)	28 1/8" (74 cm)	32 7/8" (83.5 cm)
KRFF305E (25.2 cu. ft.)	70 1/8" (178.1 cm)	68 7/8" (174.9 cm)	48 1/8" (122.2 cm)	53 1/8" (134.9 cm)	35 1/8" (90.2 cm)	33" (83.8 cm)	29 1/8" (74 cm)	35 7/8" (91.1 cm)

### LOCATION REQUIREMENTS



To ensure proper ventilation for your refrigerator, allow for a 1/8" (1.25 cm) space on each side and at the top. Allow for 1" (2.54 cm) of space behind the refrigerator. If your refrigerator has an ice maker, make sure you leave some extra space at the back for the water line connections.

If you are installing your refrigerator next to a fixed wall, leave 2 1/8" (6.3 cm) minimum on the hinge side (some models require more) to allow for the door to swing open.

**NOTE:** This refrigerator is intended for use in a location where the temperature ranges from a minimum of 55°F (13°C) to a maximum of 110°F (43°C). The preferred room temperature range for optimum performance, which reduces electricity usage and provides superior cooling, is between 60°F (15°C) and 90°F (32°C). It is recommended that you do not install the refrigerator near a heat source, such as an oven or radiator.