



16 cu. ft. Top-Freezer Refrigerator with More Storage Capacity

ART316TFDW

Available Finishes/Colours

ART316TFDW
White

Dimensions	
Depth	31 1/4
Height	65 7/8
Width	28

AHAM Volumes And Shelf Area	
Freezer Volume (Cu Ft)	4.03
Refrigerator Volume (Cu Ft)	11.95

Details	
Cooling Type	Dual Evaporator
Door Style	Flat

Exterior	
Cabinet Color	White

Exterior	
Cabinet Finish	Textured
Door Color	White
Door Finish	Textured
Handle Material	Plastic
Door Opening	Right
Handle Type	Pocket Handle
Door Style	Flat
Handle Color	White
Levelers	2 Black
Wheels	4-Natural
Hidden Hinge	No
Reversible Door	Yes

Appearance	
Cabinet Finish	Textured
Handle Material	Plastic
Door Style	Flat

- Top Features
- Dairy Center
- Gallon Door Storage Bins
- Glass Shelves

Manuals & Literature:

[Dimension Guide](#)

[Energy Guide](#)

[Installation Guide](#)

[Use and Care Guide](#)

[Warranty Information](#)

Amana® Top Mount Refrigerator

PRODUCT MODEL NUMBERS

ART104TFD
ART106TFD
ART316TFD


Electrical: A 115-volt, 60-Hz, AC-only, 15- or 20-amp fused, grounded electrical supply is required. It is recommended that a separate circuit serving only your refrigerator be provided. Use an outlet that cannot be turned off by a switch. Do not use an extension cord.

Water: A cold water supply with water pressure between 30 and 120 psi (207 and 827 kPa) is required to operate ice maker and water dispenser. If you have questions about your water pressure, call a licensed, qualified plumber.

IMPORTANT: The pressure of the water coming out of a reverse osmosis system going to the water inlet valve of the refrigerator needs to be between 30 and 120 psi (207 and 827 kPa).


Reverse Osmosis Water Supply: If a reverse osmosis water filtration system is connected to your cold water supply, the water pressure to the reverse osmosis system needs to be a minimum of 40 to 60 psi (276 to 414 kPa).

PRODUCT DIMENSIONS



Model Number	Model Size	Reversible Door	Depth - With Door "A"	Cab. Width "B"	Depth - Cabinet Only "C"	Cab. Height "D"	Overall Height "E"	Depth Door Open 90° "F"
ART104TFD	14.3 cu. ft.	Yes	30" (76.2 cm)	28" (71.1 cm)	25 1/2" (64 cm)	62 3/4" (158.4 cm)	62 7/8" (159.7 cm)	56 3/4" (144.1 cm)
ART106TFD ART316TFD	16 cu. ft.	Yes	31 1/2" (79.4 cm)	28" (71.1 cm)	25 1/2" (64 cm)	65 3/4" (166 cm)	65 7/8" (167.3 cm)	56 3/4" (144.1 cm)

LOCATION REQUIREMENTS



To ensure proper ventilation for your refrigerator, allow for a 1/2" (1.25 cm) space on each side. Allow 3" (7.5 cm) of space between overhead cabinets and refrigerator top. Allow at least 1" (25.40 mm) between back of cabinet and the wall. If your refrigerator has an ice maker, make sure you leave some extra space at the back for the water line connections.

If you are installing your refrigerator next to a fixed wall, leave enough space on the hinge side to allow for the door to swing open.

NOTE: This refrigerator is intended for use in a location where the temperature ranges from a minimum of 55°F (13°C) to a maximum of 110°F (43°C). The preferred room temperature range for optimum performance, which reduces electricity usage and provides superior cooling, is between 60°F (15°C) and 90°F (32°C). It is recommended that you do not install the refrigerator near a heat source, such as an oven or radiator.